

Casing Capping

Casing Capping is one of the oldest and simplest wiring system all over the world and also known as cable trunking , PVC profile , casing patti .Harson Casing Capping are manufactured from a specially formulated unplasticised polyvinyl chloride on fully automatic twin screw technology delivering high mechanical and impact strength profiles

Product Features

Virgin Suspension Grade PVC of K-67

Flame Retardant properties

Secure and Firm Locking

Corrosion Free Material

Durable and Impact Resistant

Application Range

Used to enclose and protect unconcealed wiring

Wiring protection in all kind of buildings

Installed where easy & frequent maintenance of wiring is required



Technical Specification Of Casing & Capping

S.No	Nominal Size (mm)	Max. Outside Diameter (mm)	Min. Outer Diameter (mm)	Tolerance Of Outside Diameter (mm)	Min. Internal Diameter (mm)	Wall Thickness (mm)
Double Lock						
1	20 x 12	20 x 12	19.8 x 11.90	0.20	18.80 x 10.80	1.00
2	25 x 16	25 x 16	24.75 x 15.85	0.30	23.60 x 14.65	1.20
3	30 x 15	30 x 15	29.75 x 14.85	0.30	28.35 x 13.40	1.20
4	38 x 20	38 x 20	37.75 x 19.85	0.30	36.40 x 18.40	1.20
Single Lock						
5	32 x 12	32 x 12	31.75 x 11.85	-0.20	30.6 x 10.80	1.2

Standard Packaging

Length of each casing is 2 meters which are packed as 100 pc in recyclable polythene bundles



* This data is indicative and may be revised without prior information